

## Self-Adhesive Drywall Tape

This tape is widely used in joining plaster plates, mending drywall cracks and piecing together and making up different kinds of plates.



It goes on faster, adheres better, and requires no pasting or stapling. It won't tear, shrink, stretch or bubble, while it hides joints, cracks and holes permanently.

The product is woven with C-glass fiberglass and is treated with a coating and contact adhesive material. Characteristics are high tensile strength, good dimensional stability, stability to temperature, good elasticity, capillary action, and corrosion resistance.

### Specifications

- Style- CET65 --- 9x9
- Tensile Strength - N/50mm
- Warp ->570
- Weft ->430
- Weight (g/m2)- 65
- Weight (oz/sq yd)- 1.88
- Finish- Corrosion resistant and contact adhesive
- Ignition loss - 18% +/- 10% or to customer requirements
- Weave - Leno
- Testing - ASTM D579
- Width (mm) - 25, 35, 50, 75, 100, 150, 200, 300 and 1000
- Width (inch)- 1", 1-3/8", 2", 3", 4", 6", 8", 12" and 40"
- Roll length (meters) - 20, 45, 50, 70, 75, 90, 150 or according to requirements
- Roll length (yards) - 21, 49, 55, 76, 82, 98, 164 or according to requirements
- ISO-9002 certified by Quality Systems Registers Inc (QSR).

### Packaging

